

Micro Converter SDI to HDMI 3G wPSU



\$59

This model has been specifically designed for professional monitoring. It includes a 17 point 3D LUT for color calibrating any monitor, projector or television. You can even output the 3D LUT on the SDI loop output! Plus it supports DCI formats and film rates including 1080p24, 1080p47.95 and 1080p48. Includes 100 to 240V AC power supply with international socket adapters.

Connections

SDI Video Inputs

1 x SD, HD or 3G-SDI.

HDMI Outputs

HDMI Type A out.

Updates, Configurations and Power


USB Type-C.

SDI Video Outputs

1 x SDI loop out.

Multi Rate Support

Auto detection of SD or HD.



Standards

SD Video Standards

525i59.94 NTSC, 625i50 PAL

HD Video Standards

720p50, 720p59.94, 720p60
 1080p23.98, 1080p24, 1080p25,
 1080p29.97, 1080p30, 1080p47.95,
 1080p48, 1080p50, 1080p59.94,
 1080p60
 1080PsF25, 1080PsF29.97, 1080PsF30
 1080i50, 1080i59.94, 1080i60

2K Video Standards

2Kp23.98 DCI, 2Kp24 DCI, 2Kp25 DCI,
 2Kp29.97 DCI, 2Kp30 DCI, 2Kp47.95
 DCI, 2Kp48 DCI, 2Kp50 DCI, 2Kp59.94
 DCI, 2Kp60 DCI
 2KPsF25 DCI, 2KPsF29.97 DCI,
 2KPsF30 DCI

SDI Compliance

SMPTE 259M, SMPTE 292M,
 SMPTE 296M, SMPTE 424M,
 SMPTE 425M

SDI Video Rates

SDI video connections are switchable between standard definition, 720p 1080i, 1080p and DCI high definition.

SDI Color Precision

4:2:2

SDI Color Space

YUV

SDI Auto Switching

Automatically detects SD, HD and level A or B for 3G-SDI.

HDMI Video Standards

525i59.94 NTSC, 625i50 PAL
720p50, 720p59.94, 720p60
1080p23.98, 1080p24, 1080p25,
1080p29.97, 1080p30, 1080p47.95,
1080p48, 1080p50,
1080p59.94, 1080p60
1080i50, 1080i59.94, 1080i60

HDMI Color Precision

4:2:2. A 17 point LUT can be loaded via the software utility for calibrating or improving monitor color.

HDMI Color Space

YUV

Software

Software Control

Mac™ and Windows™ software upgrade via USB.

Internal Software Upgrade

Via USB.

Operating Systems



Mac 10.15 Catalina,
Mac 11.1 Big Sur or later.



Windows 10, 64-bit.

Settings Control

Via software utility.

Power Requirements

Power Supply

+5V universal power supply included with international socket adapters for most countries.

Power Consumption

1.6 W

Operational Voltage Range

4.4V to 5.25V DC

Environmental Specifications

Operating temperature

0° to 40° C (32° to 104° F)

Storage temperature

-20° to 60° C (-4° to 140° F)

Relative Humidity

0% to 90% non-condensing

Physical Specifications



What's Included

Micro Converter SDI to HDMI 3G wPSU
+5V universal power supply with international socket adapters

Warranty

3 Year Limited Manufacturer's Warranty.

All items on this website are copyright Blackmagic Design Pty. Ltd. 2021, all rights reserved. All trademarks are property of their respective owners. MSRP includes duties, but excludes sales tax and shipping costs. This website uses remarketing services to advertise on third party websites to previous visitors to our site. You can opt out at any time by changing cookie settings. [Privacy Policy](#)

Blackmagic Design Authorized Reseller